

Reifen	Dimension	Li	Geschw.Kl.	Extraktions(XL)	Rad	IS [mm]	Stahlfeld	LM-Rad	Schneckeite midgi (mA)	BMW 5er Touring (F11)									
										518d	520d/xd	520i	525d/xd	528i/xi	530d/dx	535i/xi	535d/xd	550i	M550xd
<b>Sommer:</b>										B47D20O0	B47D20O0	N20B20U0	N47D20T1	N20B20O0	N57D30O1	N55B30M0	N57D30T1	N63B44O1	N57D30S1
225/55 R17	97	W	x	8Jx17 EH2+	30	x x	x	x	-										
225/55 R17	97	Y	x	8Jx17 EH2+	30	x x	-	-	-					x	x	x	x	-	
225/55 R17	97	Y	x	8Jx17 EH2+	30	x x	x	x	x				x	x	x	x	-	-	
245/45 R18	96	Y	x	8Jx18 EH2+	30	x x	x	x	x				x	x	x	x	x	-	
245/40 R19 XL	98	Y x	x	8,5Jx19 EH2+	33	x	x	x	x				x	x	x	x	x	x	
VA: 245/35 R20 XL	95	Y x	x	8,5Jx20 EH2+	33	x	x	x	x				x	x	x	x	x	x	
HA: 275/30 R20 XL	97	Y x	x	9Jx20 EH2+	44	x	x	x	x				x	x	x	x	x	x	
<b>Winter:</b>																			
225/55 R17	97	H	x x	8Jx17 EH2+	30	x x	x	x	x				x	x	x	x	-	-	
225/55 R17	97	H	x x	8Jx17 EH2+	30	x x	x	x	x				x	x	x	x	-	-	
245/45 R18 XL	100	V x x	x	8Jx18 EH2+	30	x x	x	x	x				x	x	x	x	x	x	
<b>Reserverad:</b>																			
135/90 R17	104	M		4Bx17 H2	5	x	x	x	x				x	x	x	x	-	-	

- = nicht freigegeben

X = zulässige Rad-/Reifendimension

Radschrauben: M14x1,25  
Anzugsmoment:  $M_A = 140 \pm 10 \text{ Nm}$